

浙大三色

Email:sensing@sensingm.com

Tel:+86 571 85021543 Fax:+86 571 87977635

---

## ROLED

---

灯具名称: 投光灯

灯具描述: F1223A1-9-36DC-RC-Y(60-CL-9RGBWN-AJ, CT)

报告编号:

电压(V): 36.2000

测试编号: 20210302016

电流(A): 0.3820

光源规格型号: CL

功率(W): 13.8000

每个光源光通量(lm)

功率因数: 1.0360

光源数量: 9

镇流器型号:

发光面长度(mm): 110

发光面宽度(mm): 110

测试模式: C

发光面高度(mm): 0

## 光度结果

---

灯具光通量(lm): 521.78

灯具效能(lm/w): 37.81

中心光强(cd): 485.519

最大光强(cd): 560.492

最大光强角度:  $C=270.0 \gamma=10.0$

半峰边角(50%Imax): [C0/180]Total=56.6

[C90/270]Total=57.4

光束扩散角(10%Imax): [C0/180]Total=100.2



[C90/270]Total=101.1

---


测试设备: GMS1800  
环境温度(°C): 25.0

测试日期: 2021/3/2  
环境湿度(%): 60.0%

测试人员: anpeilou  
测试距离(m): 8.76




C270(Max): —  
C0/C180: —  
C90/C270: —



Max , Ave C270面光束角60.14

ROLED 投光灯  
平面等照度曲线



(10%Emax) 5.930767	—
(20%Emax) 11.86156	—
(30%Emax) 17.79233	—
(40%Emax) 23.723	—
(50%Emax) 29.65378	—
(60%Emax) 35.58455	—
(70%Emax) 41.51534	—
(80%Emax) 47.44611	—
(90%Emax) 53.37689	—

测试设备: GMS1800  
环境温度(°C): 25.0

测试日期: 2021/3/2  
环境湿度(%): 60.0%

测试人员: anpeilou  
测试距离(m): 8.76

# ROLED 投光灯

## 灯具的亮度限制曲线(灯具无发光侧边)

亮度值表


$\gamma$	45	50	55	60	65	70	75	80	85
C0	8960	6729	5175	4021	3286	2818	2475	2155	1601
C45	0	0	0	0	0	0	0	0	0
C90	7911	6107	4777	3881	3271	2781	2524	2228	1601

L横(65)	L纵(65)	L45(65)	L横(75)	L纵(75)	L45(75)	L横(85)	L纵(85)	L45(85)
2896	3264	0	1960	2401	0	1055	1164	0

眩光等级表

眩光等级	质量等级	使用照度(lx)							
1.15	A	2000	1000	500	$\leq 300$				
1.5	B		2000	1000	500	$\leq 300$			
1.85	C			2000	1000	500	$\leq 300$		
2.2	D				2000	1000	500	$\leq 300$	
2.55	E					2000	1000	500	$\leq 300$
		a	b	c	d	e	f	g	h

亮度限制曲线



参照UGR的照射评估											
天花板反射率	70	70	50	50	30	70	70	50	50	30	
墙壁反射率	50	30	50	30	30	50	30	50	30	30	
地板反射率	20	20	20	20	20	20	20	20	20	20	
空间尺寸		Viewed crosswise					Viewed endwise				
X	Y										
2H	2H	16.46	17.64	16.82	17.95	18.27	16.13	17.32	16.50	17.63	17.95
	3H	17.40	18.45	17.78	18.78	19.14	16.98	18.03	17.36	18.36	18.72
	4H	17.73	18.70	18.13	19.05	19.44	17.24	18.22	17.65	18.57	18.96
	6H	17.94	18.83	18.35	19.20	19.60	17.40	18.29	17.82	18.67	19.06
	8H	17.98	18.82	18.41	19.21	19.62	17.43	18.27	17.86	18.66	19.07
	12H	18.01	18.82	18.45	19.20	19.63	17.46	18.26	17.89	18.65	19.08
4H	2H	16.70	17.67	17.10	18.02	18.41	16.42	17.39	16.82	17.74	18.13
	3H	17.84	18.64	18.26	19.04	19.45	17.45	18.25	17.87	18.65	19.06
	4H	18.27	18.98	18.70	19.40	19.84	17.82	18.53	18.26	18.95	19.39
	6H	18.52	19.13	18.99	19.58	20.05	18.02	18.63	18.49	19.08	19.55
	8H	18.59	19.16	19.06	19.61	20.08	18.08	18.65	18.55	19.09	19.57
	12H	18.64	19.13	19.13	19.62	20.10	18.12	18.61	18.61	19.10	19.58
8H	4H	18.36	18.92	18.83	19.37	19.85	17.95	18.51	18.42	18.96	19.44
	6H	18.71	19.16	19.21	19.66	20.15	18.26	18.72	18.76	19.21	19.70
	8H	18.82	19.23	19.35	19.75	20.25	18.37	18.77	18.89	19.29	19.79
	12H	19.43	19.79	19.95	20.29	20.86	18.98	19.34	19.50	19.83	20.41
12H	4H	18.34	18.83	18.82	19.32	19.79	17.93	18.43	18.42	18.92	19.39
	6H	19.16	19.12	19.24	19.59	20.13	18.72	18.68	18.80	19.15	19.69
	8H	18.86	19.22	19.38	19.71	20.29	18.41	18.77	18.93	19.27	19.85
对应照射距离，改变观察者位置S											
S = 1.0H	1.0/-1.3					1.1/-1.4					
S = 1.5H	2.0/-1.9					2.2/-2.0					
S = 2.0H	3.8/-2.1					4.1/-2.3					
标准表格	BK2					BK2					
更正系数	-0.4					0.0					

# ROLED 投光灯

## 光强数据表(cd)

附页 第 7页 共7页

C/γ(°)	0.0	5.0	10.0	15.0	20.0	25.0	30.0	35.0	40.0
0.0	485.52	481.53	466.87	436.33	379.16	303.57	227.37	159.69	110.73
30.0	492.58	468.41	441.24	409.16	359.59	293.14	220.85	154.63	107.13
60.0	489.43	452.14	419.06	383.84	335.57	268.20	200.13	140.81	95.92
90.0	494.04	452.60	416.38	382.08	334.42	267.66	201.21	141.43	98.61
120.0	487.82	452.91	418.60	381.69	328.05	256.38	188.39	130.61	91.09
150.0	488.82	468.02	442.16	403.95	346.93	271.11	196.29	137.97	95.92
180.0	485.52	484.14	468.25	428.58	362.97	283.47	204.66	143.42	98.91
210.0	492.58	510.92	505.39	464.49	389.06	295.67	208.27	142.73	97.84
240.0	489.43	528.34	543.00	515.06	440.78	339.10	244.10	168.75	112.96
270.0	494.04	538.70	560.49	534.55	455.67	357.44	259.99	177.03	118.79
300.0	487.82	525.58	547.29	529.49	462.80	368.11	267.43	187.47	126.23
330.0	488.82	507.85	509.15	481.61	414.15	326.67	239.57	164.91	114.19
360.0	485.52	481.53	466.87	436.33	379.16	303.57	227.37	159.69	110.73
C/γ(°)	45.0	50.0	55.0	60.0	65.0	70.0	75.0	80.0	85.0
0.0	76.66	52.34	35.91	24.33	16.81	11.66	7.75	4.53	1.69
30.0	73.21	51.34	35.76	25.17	17.88	12.58	8.90	5.53	2.46
60.0	66.38	46.96	33.23	23.17	16.73	12.12	8.13	4.91	2.07
90.0	67.68	47.50	33.15	23.48	16.73	11.51	7.90	4.68	1.69
120.0	63.00	44.28	30.70	21.64	15.42	10.82	7.06	4.22	1.30
150.0	65.99	46.27	32.46	22.33	14.43	8.29	5.37	3.99	1.30
180.0	66.61	43.89	28.55	19.11	12.82	8.36	4.53	2.15	0.54
210.0	66.38	45.89	31.23	21.33	14.73	9.90	6.37	3.15	0.54
240.0	77.74	53.41	35.45	23.94	16.19	11.13	6.68	3.68	0.61
270.0	80.96	55.10	37.06	24.94	16.65	10.97	7.14	3.53	0.77
300.0	86.94	59.63	39.44	26.32	17.73	11.97	7.44	4.37	1.15
330.0	77.97	53.87	36.76	24.94	16.96	11.20	7.44	4.14	1.38
360.0	76.66	52.34	35.91	24.33	16.81	11.66	7.75	4.53	1.69
C/γ(°)	90.0								
0.0	0.08								
30.0	0.15								
60.0	0.08								
90.0	0.00								
120.0	0.00								
150.0	0.00								
180.0	0.00								
210.0	0.00								
240.0	0.00								
270.0	0.00								
300.0	0.00								
330.0	0.00								
360.0	0.08								